



Cool Everywhere

2024





T-Pro Series



SMART CONTROL
Control your AC using your smart home assistant or your cellphone.



Sleep Mode

Once activated, Sleep Mode will run at lower capacity; maintaining a narrow temperature buffer. Fan speed slows down for energy efficient performance through the night. Display light also turns off in order to not disturb sleep.



Auto Restart

Upon loss of power from power outage this unit will auto restart and resume cooling the space.



Zinc Plated

Increases the underlying metals lifespan thus ensuring efficient and corrosion free usage.



20-SEER Efficiency

Save money and enjoy energy efficiency with Smart Inverter.
*Inverter models only.



Quiet Operation

Indoor and Outdoor units have been designed to reduce noise and vibration during operation.



Gentle Breeze Mode

More than one thousand of perfectly placed 2-3mm micro-holes are arranged on S-shaped vanes, dispersing air more evenly throughout the room. * Inverter models only.



Effortless Cleaning


An intuitive cleaning design makes it simpler to take apart and reassemble. 4 Key components: Filter, vanes, plate and flap easily disassemble and fit back together for manual cleaning.

SPECIFICATIONS

Specifications	MRD-12CSA/T	MRD-12CSA/T	MRD-18CSA/T	MRD-18CSA/T	MRD-24CSA/T	MRD-24CSA/T
Cooling Capacity	12,000 BTU/h	12,000(2047-12625)BTU/h	18,000BTU/h	18000(4095 - 21155)BTU/h	24000BTU/h	24000(5118-24900)BTU/h
Refrigerant	R410A/0.490KG	R410A/0.720KG	R410A/0.870KG	R410A/0.860KG	R410A/0.840KG	R410A/1.150KG
Outdoor noise level (dB)	51	52	58	55	54	52
Indoor noise level (dB)	40	39	44	45	47	48
Power supply				208-230V		
Current	5.9A	5.0(1.0-7.0)A	8.8A	7.9(1.3 - 12.0)A	11.7A	10.9(1.7-13.0)A
Rated current (IEC/EN60335)	7.7A	7.0A	11.5A	12.0A	15.2A	13.0A
Product type	COOLING					
Power Input	1255W	1045(220-1500)W	2450W	1666(300 - 2300)W	2450W	2285(350 - 2450)W
Rated Power Input (IEC/EN60335)	1635W	1500W	2400W	2300W	3185W	2450W
SEER	12	20	12	20	12	20
Weight Outdoor	55 LB	52.9 LB	70.5 LB	64 LB	92.5 LB	79 LB
Weight Indoor	17.6 LB	22 LB	24.2 LB	23 LB	30.8 LB	30.8 LB
Rated Frequency	60Hz					
Outdoor water proof protection	IPX4					
Copper tubing size	3/8" & 1/4"	3/8" & 1/4"	1/2" & 1/4"	3/8" & 1/4"	5/8" & 1/4"	1/2" & 1/4"
Warranty	1 Year					
Gold fins	Yes					
Length of Copper Tubing	10ft Included					
Accessories	Remote w/ Holder, Anti-Vibration Rubber Pads, Indoor Bracket and Drain Hose					



T-Pro Series



Effortless Cleaning

An intuitive cleaning design makes it simpler to take apart and reassemble. 4 Key components: Filter, vanes, plate and flap easily disassemble and fit back together for manual cleaning.



Auto Restart

Upon loss of power from power outage this unit will auto restart and resume cooling the space.



Zinc Plated

Increases the underlying metals lifespan thus ensuring efficient and corrosion free usage.



20-SEER Efficiency

Save money and enjoy energy efficiency with Smart Inverter.



Quiet Operation

Indoor and Outdoor units have been designed to reduce noise and vibration during operation.



Gentle Breeze Mode

More than one thousand of perfectly placed 2-3mm micro-holes are arranged on S-shaped vanes, dispersing air more evenly throughout the room.



Smart Control

Control your AC using your smart home assistant or your cellphone.

SPECIFICATIONS

Specifications	MRD-12CSAI/T32	MRD-18CSAI/T32	MRD-24CSAI/T32
Cooling Capacity	12,000(1910-13170) BTU/h	18000(3410 - 18770)BTU/h	24000(5120-23885)BTU/h
Refrigerant	R32A/0.450KG	R32A/0.510KG	R32A/0.690KG
outdoor noise level (dB)	53	55	52
Indoor noise level (dB)	41	41	49
Power supply	208-230V		
Current	8.0(1.5-8.0)A	12.0(1.6-12.0)A	13.0(1.5-13.0)A
Rated current (IEC/EN60335)	8.0A	12.0A	13.0A
Product type	Cooling		
Power Input	1170(180-1700)W	1755(300 - 2100)W	2340(350 - 2400)W
Rated Power Input (IEC/EN60335)	1700W	2100W	2400W
SEER	20	20	20
Weight Outdoor	46.3 LB	57.3 LB	61.7 LB
Weight Indoor	17.6 LB	23.1 LB	26.5 LB
Rated Frequency	60Hz		
Outdoor water proof protection	IPX4		
Copper tubing size	3/8" & 1/4"	1/2" & 1/4"	1/2" & 1/4"
Warranty	1 Year		
Gold fins	Yes		
Length of Copper Tubing	10ft Included		
Accessories	Remote w/ Holder, Anti-Vibration Rubber Pads, Indoor Bracket and Drain Hose		



XA Series



Quiet Operation

Indoor and Outdoor units have been designed to reduce noise and vibration during operation.



Auto Restart

Upon loss of power from power outage this unit will auto restart and resume cooling the space.



Zinc Plated

Increases the underlying metals lifespan thus ensuring efficient and corrosion free usage.



Sleep Mode

Once activated, Sleep Mode will run at lower capacity; maintaining a narrow temperature buffer. Fan speed slows down for energy efficient performance through the night. Display light also turns off in order to not disturb sleep.



5-Speed

5 Speed fan levels allows the AC to run at the speed needed to cool the space and create comfort.

SPECIFICATIONS

Specifications	MRD-36CSA/XA	MRD-36CSAI/XA
Cooling Capacity	36000BTU/h	36000(7506 - 37532)BTU/h
Refrigerant	R410A/2.000KG	R410A/2.450KG
Outdoor noise level (dB)	60	61
Indoor noise level (dB)	52	51
Power supply	208-230V	
Current	15.4A	17.4(2.7 - 20.5)A
Rated current (IEC/EN60335)	20.0A	20.5A
Product type	COOLING	
Power Input	3405W	4000(390 - 4200)W
Rated Power Input (IEC/EN60335)	4430W	4200W
SEER	13	19
Weight Outdoor	130 LB	114.6 LB
Weight Indoor	39.6 LB	38.5 LB
Rated Frequency	60Hz	
Outdoor Waterproof Protection	IPX4	
Copper tubing size	1/4" & 5/8"	1/4" & 5/8"
Warranty	1 Year	
Gold fins	Yes	
Length of Copper Tubing	10ft Included	
Accessories	Remote w/ Holder, Anti-Vibration Rubber Pads, Indoor Bracket and Drain Hose	



Cassette



Sleep Mode

Once activated, Sleep Mode will run at lower capacity; maintaining a narrow temperature buffer. Fan speed slows down for energy efficient performance through the night. Display light also turns off in order to not disturb sleep.



Auto Restart

Upon loss of power from power outage this unit will auto restart and resume cooling the space.



Drainage Pump

Built in Drainage Pump allows for the condensing water to be lifted up to 750mm which is convenient for installation.



Quiet Operation

Indoor and Outdoor units have been designed to reduce noise and vibration during operation.



Air Branches

Air branch opening on the unit allows for the unit to distribute cool air to a small space like study room or office when needed.



Wire Control

Wire control is available, which is especially handy for hotel rooms and offices where you might not want a wireless remote. *Optional

SPECIFICATIONS

Specifications	MRD-36CRA/U2-C	MRD-36CCRA/U2-C	MRD-36CCRA/DV25PQB	MRD-48CCRA/U2-C
Cooling Capacity	24,000 BTU/h (2 ton)	36,000 BTU/h (3 ton)	36,000 BTU/h (3 ton)	48,000 BTU/h (4 ton)
Refrigerant	R410A/2.60kg	R410A/1.630kg	R410A/2.58kg	R410A/2.60kg
Outdoor noise level (dB)	60dB	60dB	65dB	62dB
Indoor noise level (dB)	44dB	47dB	53dB	47dB
Power supply	11.1A	17.6A	19.0A	22.8A
Current	11.1A	17.6A	19.0A	22.8A
Rated current (IEC/EN60335)	18.2A	22.0A	20.0A	36.0A
Product type				Cooling
Outdoor unit size inches WxLxH	22x22x25	22x22x30	29x29x25	29x29x33
Indoor unit size inches WxLxH	33x33x9	33x33x11.5	33x33x11.5	33x33x11.5
Power Input	2420W	4138W	4220W	5347W
Rated Power Input (IEC/EN60335)	3350W	5000W	4400W	7500W
SEER	12	12	18	12
Weight Outdoor	98lb	110.2lb	119lb	169.7lb
Weight Indoor	57lb	61.7lb	61.7lb	66lb
Rated Frequency				60Hz
Outdoor water proof protection				IPX4
Copper tubing size	3/8" & 5/8"	3/8" & 3/4"	3/8" & 3/4"	3/8" & 3/4"
Warranty				1 Year
Length of Copper Tubing				Tubing not included
Accessories				Remote

Specifications	MRD-60CRA/U2-C	MRD-55CCRA/DV25PQB	MRD-60CCRA/U6-C
Cooling Capacity	55,000 BTU/h (5 ton)	55,000 BTU/h (5 ton)	MRD-60CCRA/U2-C (5 ton)
Refrigerant	R410A/2.35kg	R410A/4.10kg	R410A/2.250kg
Outdoor noise level (dB)	62dB	67dB	66dB
Indoor noise level (dB)	47dB	54dB	47dB
Power supply			220V 3-PHASE
Current	26.3A	30A	14.6A
Rated current (IEC/EN60335)	40.0A	35A	22.0A
Product type			
Outdoor unit size inches WxLxH	29x29x33	29x29x33	29x29x33
Indoor unit size inches WxLxH	33x33x11.5	33x33x11.5	33x33x11.5
Power Input	6153W	6500W	5100W
Rated Power Input (IEC/EN60335)	8000W	7700W	6750W
SEER	12	18	12
Weight Outdoor	169.8lb	158.7lb	163lb
Weight Indoor	66.1lb	64lb	66lb
Rated Frequency			
Outdoor water proof protection			
Copper tubing size	3/8" & 3/4"	3/8" & 7/8"	3/8" & 3/4"
Warranty			1 Year
Length of Copper Tubing			Tubing not included
Accessories			Remote

Parts & Warranty



REFRIGERANTS



Warranty:


All of our units come with a 1-year warranty in the case a unit comes with a factory defect.

Parts:

Should there be any failure in the unit due to unforeseen circumstances. We stock a wide selection of parts for our units. We also offer technical support by our certified technicians.

 <p>R134A-340GRMER Refrigerant Meridian R134A 340gr Case Qty: 12</p>	 <p>R134A-1KGMER Refrigerant Meridian R134A 340gr Case Qty: 12</p>	 <p>R134A-30LBMER Refrigerant Meridian R134A 30lb Case Qty: 1</p>	 <p>R404A-24LBMER Refrigerant Meridian R404A 24lb Case Qty: 1</p>
 <p>R410A-650GRMER Refrigerant Meridian R410A 650gr Case Qty: 12</p>	 <p>R410A-25LBMER Refrigerant Meridian R410A 25lbs Case Qty: 1</p>	 <p>R600A-420GRMER Refrigerant Meridian R600A 420gr Case Qty: 12</p>	

AC Protection



UN1950
AC Protective
Coating Aerosol
400ML



UN1263
AC Protective
Coating Liquid
1 Liter

All-in-one corrosion and complete HVAC protection coating.

This protective coating creates a robust barrier for humid, salt laden air and pests such as lizards, frogs and other critters that may damage your PCB. It also strongly protects against corrosion on new evaporator coils.

Uncoated

Coated



Total Rust & PCB Protection

- ✓ Smooth & clear finish
- ✓ Stable UV inhibitors
- ✓ Retains flexibility to expand & contract with heat cycles
- ✓ None conductive to electricity, but allows heat transfer
- ✓ Tested to ASTM standards to exceed 764 hours Salt chamber testing
- ✓ Manufactured in an ISO9001 and ISO14001 facility
- ✓ Approved for use by multiple manufacturers



OUR BRANCHES

SPANISH LOOKOUT

BELIZE CITY

BELMOPAN

ORANGE WALK

DANGRIGA

PUNTA GORDA

CONTACT US

823-0104

sales@westracbelize.com

www.westrac.bz

